



Bulldog
HOSE COMPANY



HI-COMBAT II®

Ultimate Aggressive Interior Attack Fire Hose

Hi-Combat II® is the ultimate in firefighting hose technology for aggressive interior combat operations. Its unique design gives combat firefighters the performance, flexibility, and endurance to deal with the toughest challenges. A special weave, high-tech nylon-polyester outer jacket encases an inner lining consisting of a one-piece, extruded-through-the-weave hose for optimum performance and reliability.

With high-visibility material woven right into the hose, firefighters can follow the "exit" and arrow markings to safety. Bulldog can also add up to 32 custom characters sewn into the hose.* Hi-Combat II is available in 5 NFPA colors that are extruded through the weave, not dyed, and will not bleed or wear off. It combines higher heat, abrasion and chemical resistance with unmatched kink resistance and superior ease of drag.

Engineered by Bulldog, Hi-Combat II is guaranteed to meet specified burst pressure and exceed the NFPA 1961 standard. Hi-Combat II's super powerful attributes set standards for fire hose that every firefighter deserves.

**Available on 1-3/4" and 2" only. 1000' minimum order requirement.*

UNIQUE DESIGN FEATURES:

- Colors are extruded through the weave, not dyed, and will not bleed or wear off
- High-visibility safety material
- Available in 5 NFPA colors
- High abrasion resistance
- High heat resistance
- Chemical resistance
- Superior ease of drag

*Backed by Bulldog's Municipal
Fire Hose Ten-Year Warranty.
bulldoghose.com/resources*



Raise your firefighting standards!

Contact us today: 712.655.9201 · bulldoghose.com

AMERICAN MADE TOUGH.™

FEATURES:

**Designed for Aggressive
Interior Combat Operations**

Minimized Friction Loss

Excellent Kink Resistance
Kink resistance exceeds that of
conventional jacketed hose.

Superior Abrasion Performance
Abrasion-resistant outer jacket
is designed and manufactured
to withstand a minimum of
2,000 cycles on the U.L. abrasion
test and 12,000 cycles on the
F.M. abrasion test programs.

Lowest Drag Coefficient
Drag coefficient is the lowest of
any fire hose BullDog has tested,
making it easier to advance
during attack operations.

**Ideal for Personal Portable
Monitors and High-Rise
Firefighting Operations**

Anti-Burst Technology
Ensures it will not burst
catastrophically – even with
a 1/2" diameter hole through
both the jacket and liner.



Exceeds Standards
Hi-Combat II® is manufactured to
meet or exceed the NFPA 1961 standard.

Chemical-Resistant Liner
Protects from exposure to
water and contamination by
most chemical substances,
hydrocarbons, oil and grease.

Temperature range -36°F to +158°F

ULC
Available on 1-3/4" and 2-1/2".

TECHNICAL SPECIFICATIONS:

Size	Pressure						Bowl Size	Weight (50'/15M)	Coil Diameter (50'/15M)		
	Service		Proof		Burst						
inch mm	psi	kpa	psi	kpa	psi	kpa	inch	lbs	kg	inch	mm
1-3/4 45 	500	3,500	1,000	7,000	1,500	10,500	2-1/8	18	8.1	16.5	419
2 50	500	3,500	1,000	7,000	1,500	10,500	2-3/8	20	9.07	17.5	445
2-1/2 65 	500	3,500	1,000	7,000	1,500	10,500	2-7/8	23	10.4	18.5	470

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.



*Available on 1-3/4" and 2" only.
1000' minimum order requirement.