



**Bulldog**  
HOSE COMPANY



# DRAG HOSE™

## Sludge Injection Drag Hose

Bulldog Drag Hose™ is a high performance flexible lay flat hose for sludge injection and transfer of slurries, liquid manure and municipal sludge. Designed for both continuous and intermittent operation at high working pressures. Drag Hose's through-the-weave manufacturing technique prevents delamination and results in a much lower friction loss than aluminum or PVC pipe, reducing pumping costs. Swells in diameter enabling fluids to be pumped further and at higher flow rates. Raw materials, components and finished products are rigorously tested and inspected to ensure excellent product reliability.

### TYPICAL APPLICATIONS:

- Sludge injection
- Slurry transfer
- Municipal sludge
- Liquid manure

### UNIQUE DESIGN FEATURES:

- Lower friction loss
- Reduces pumping costs
- Higher flow rates and further pumping distance
- Fast deployment and retrieval



*Backed by Bulldog's Irrigation  
Hose One-Year Warranty.  
[bulldoghose.com/resources](http://bulldoghose.com/resources)*



**Step up your fluid delivery!**

Contact us today: 800.667.0423 · [bulldoghose.com](http://bulldoghose.com)

**AMERICAN MADE TOUGH.™**

## FEATURES:

**Improved Packability**  
Lightweight and compact for economical storage.

**Ease of Drag**  
Specifically designed to be pulled and dragged behind sludge injection vehicles that inject liquids into the soil for agricultural gain.

**Superior Abrasion Performance**  
Durable, abrasion resistant thermoplastic polyurethane construction for tough environments.

**Unmatched Performance**  
Long, continuous lengths can be quickly deployed and retrieved using light duty or power-driven reels.

**Extreme Durability**  
Features "Through-the-Weave" construction comprising a circular woven high tenacity polyester reinforcement, totally encapsulated in a tough, abrasion resistant, polyurethane cover and lining.

## TECHNICAL SPECIFICATIONS:

Size	Pressure		End Tensile Strength	Weight
	Working	Burst		
inch mm	psi kpa	psi kpa	lbs kg	lbs/ft kg
5 125	250 1724	500 3447	40,000 18181	1.15 0.52
5-1/2 140	250 1724	500 3447	46,000 20909	1.26 0.57
6 150	250 1724	500 3447	46,000 20909	1.60 0.73
7-1/4 184	250 1724	500 3447	70,000 31818	1.90 0.86

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.

