



REDSKIN/BLUESKIN

Industrial Fire Hose

Respond to fires quickly with BullDog Redskin/Blueskin. The hose is a lay-flat, lightweight, flexible firehose specifically designed for industrial fire protection. Bringing tough, versatile firefighting power to departments in industrial situations. Redskin/Blueskin is UL approved and features a unique through-the-weave, one-piece construction that will not delaminate. The synthetic reinforcement is totally encased in a nitrile-rubber cover and lining which is resistant to fuels, oils and chemicals. Dependable, lay-flat and flexible, BullDog Redskin/Blueskin firehose is specifically engineered for industrial fire protection.

UNIQUE DESIGN FEATURES:

- Lower friction loss
- Higher flow rates and further pumping distance
- Fast deployment and retrieval
- Lightweight for easy handling
- Maintenance free
- Compact for easy storage
- Resists fuels, oils, and chemicals
- Superior kink resistance
- Outstanding abrasion resistance



 **AMERICAN MADE TOUGH.™**

Contact us today: 712.655.9201 · puck.com/puck-fire



Redskin

REDSKIN/BLUESKIN



FEATURES:

Extreme Durability

Hose meets or exceeds specifications for heat and kink resistance.

Durable Construction

Lay-flat, lightweight and flexible design is really suited for industrial fire protection and in-plant apparatus.

Less Maintenance

No drying time required — just wash and store.

Long Service Life

Nitrile-rubber cover eliminates additional weight issues caused by water pick up during use and greatly increases abrasion resistance, providing a long service life. The hose is designed to resist cracking mildew and rot, which translates to a long service life.

Chemical-Resistant

Resists fuels, oils and a wide range of chemicals.

Best in Class Adhesion

Best in class adhesion provides enhanced hose performance and increased hose life.

Exceeds Standards

Redskin/Blueskin is manufactured to meet or exceed NFPA 1961 standard. UL and ULC Listed and FM Approved, inquire for details.

UL & ULC

Available on 1-1/2", 1-3/4", and 2-1/2".

TECHNICAL SPECIFICATIONS:

Size	Pressure						Bowl Size	Weight (50'/15M)	Coil Diameter (50'/15M)		
	Service		Proof		Burst						
inch mm	psi	kpa	psi	kpa	psi	kpa	inch	lbs	kg	inch	mm
1-1/2 38	300	2,100	600	4,200	900	6,300	1-3/4	11	5.0	13	330
1-3/4 45	300	2,100	600	4,200	900	6,300	2-1/16	14	6.4	13-3/4	349
2 50	300	2,100	600	4,200	900	6,300	2-5/16	18	8.2	14-1/2	368
2-1/2 65	300	2,100	600	4,200	900	6,300	2-3/4	22	10.0	14-1/2	368
3 75	300	2,100	600	4,200	900	6,300	3-5/16	30	13.6	16-1/2	419

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.

