



# ARMOUR GUARD® LDH

## Heavy-Duty, Rubber-Covered Industrial Discharge Hose

Transfer sludge and manure easily and reliably with the Bulldog Armour Guard® Hose. Designed to be a lay-flat, flexible discharge hose that brings impressive flow to any situation. It combines the lightweight, compact features of a unique nitrile/PVC blend with enhanced durability and abrasion resistance as compared to a conventional rubber hose. Armour Guard features a heavy-duty, one-piece design with all-synthetic, extruded-through-the-weave materials. This allows the hose to expand under pressure, decreasing friction loss and increases flow. The ozone-resistant synthetic rubber liner and cover totally encase and protect the high-performance synthetic woven reinforcement from the effects of abrasion, chemicals and heat. Armour Guard cleans easily and offers ease of maintenance. The standard color is yellow.

### UNIQUE DESIGN FEATURES:

- Lower friction loss
- Reduces pumping costs
- Higher flow rates and further



**Backed by Bulldog's  
Irrigation Hose One-Year Warranty.**  
[bulldoghose.com/resources](http://bulldoghose.com/resources)



**Step up your fluid delivery!**

**Contact us today:** 712.655.9201 · [bulldoghose.com](http://bulldoghose.com)

**AMERICAN MADE TOUGH.™**

**FEATURES:**

**Long Service Life**  
Nitrile-rubber extruded through-the-weave provides long-term storage stability and working life. Superior resistance to ozone and ultraviolet light.

**Durable Construction**  
Special rib pattern for exceptional abrasion and cut resistance.

**High Pressure Rating**  
Fully protected high tensile yarns for improved working pressure rating and drag resistance.

**Kink Resistant**  
Superior kink resistance.

**Best in Class Adhesion**  
Best in class adhesion provides enhanced hose performance and increased hose life.

**Perfect for Supply Lines**  
Best used as a supply line, feeder line discharge applications.

**High Visibility**  
Yellow color yields a higher level of nighttime visibility.

**Multiple Sizes**  
Available in 4", 5" and 6" hand lines.

**TECHNICAL SPECIFICATIONS:**

Size	Pressure									
	Working	Burst	End Tensile Strength		Wall Thickness		Weight			
inch mm	psi kpa	psi kpa	lbs	kg	inch	mm	lbs/ft	kg		
4 100	300 2,068	600 4,136	25,000	11,340	0.120	3.05	0.84	0.38		
5 125	300 2,068	600 4,136	36,000	16,329	0.125	3.18	1.04	0.47		
6 150	300 2,068	600 4,136	54,000	24,494	0.130	3.30	1.48	0.67		

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.



DURABLE, ABRASION  
RESISTANT THERMOPLASTIC  
POLYURETHANE MATERIAL  
PROVIDES EASE OF  
DRAG IN THE TOUGHEST  
ENVIRONMENTS

