



Bulldog
HOSE COMPANY



HI-COMBAT II

Ultimate Aggressive Interior Attack Fire Hose

Hi-Combat II is the ultimate in firefighting hose technology for aggressive interior combat operations. Its unique design gives combat firefighters the performance, flexibility, and endurance to deal with the toughest challenges. A special weave, high-tech nylon-polyester outer jacket encases an inner lining consisting of a one-piece, extruded-through-the-weave hose for optimum performance and reliability.

With high-visibility material woven right into the hose, firefighters can follow the "exit" and arrow markings to safety. Bulldog can also add up to 32 custom characters sewn into the hose.* Hi-Combat II is available in 5 NFPA colors that are extruded through the weave, not dyed, and will not bleed or wear off. It combines higher heat, abrasion and chemical resistance with unmatched kink resistance and superior ease of drag.

Engineered by Bulldog, Hi-Combat II is guaranteed to meet specified burst pressure and exceed the NFPA 1961 standard. Hi-Combat II's super powerful attributes set standards for fire hose that every firefighter deserves.

**Available on 1-3/4" and 2" only. 1000' minimum order requirement.*

UNIQUE DESIGN FEATURES:

- Colors are extruded through the weave, not dyed, and will not bleed or wear off
- High-visibility safety material
- Available in 5 NFPA colors
- High abrasion resistance
- High heat resistance
- Chemical resistance

*Backed by Bulldog's Municipal
Fire Hose Ten-Year Warranty.
bulldoghose.com/resources*



Raise your firefighting standards!

Contact us today: 712.655.9201 · bulldoghose.com

AMERICAN MADE TOUGH.™

HI-COMBAT II



FEATURES:

Designed for Aggressive Interior Combat Operations

Minimized Friction Loss

Excellent Kink Resistance

Kink resistance exceeds that of conventional jacketed hose.

Superior Abrasion Performance

Abrasion-resistant outer jacket is designed and manufactured to withstand a minimum of 2,000 cycles on the U.L. abrasion test and 12,000 cycles on the F.M. abrasion test programs.

Lowest Drag Coefficient

Drag coefficient is the lowest of any fire hose Bulldog has tested, making it easier to advance during attack operations.

Ideal for Personal Portable Monitors and High-Rise Firefighting Operations

Anti-Burst Technology

Ensures it will not burst catastrophically — even with a 1/2" diameter hole through both the jacket and liner.

Exceeds Standards

Hi-Combat II is manufactured to meet or exceed the NFPA 1961 standard.

Chemical-Resistant Liner



Protects from exposure to water and contamination by most chemical substances, hydrocarbons, oil and grease.

Temperature range -36°F to +158°F

ULC

Available on 1-3/4" and 2-1/2".

TECHNICAL SPECIFICATIONS:

Size	Pressure						Bowl Size	Weight (50'/15M)	Coil Diameter (50'/15M)		
	Service		Proof		Burst						
inch mm	psi	kpa	psi	kpa	psi	kpa	inch	lbs	kg	inch	mm
1-3/4 45 	500	3,500	1,000	7,000	1,500	10,500	2-1/8	18	8.10	16.5	419
2 50	500	3,500	1,000	7,000	1,500	10,500	2-3/8	20	9.07	17.5	445
2-1/2 65 	500	3,500	1,000	7,000	1,500	10,500	2-7/8	23	10.4	18.5	470

Bulldog Hose Company maintains ongoing product improvement and development programs. Therefore Bulldog reserves the right to modify any product or specification without prior notice. If necessary, please contact Bulldog Hose Company customer service to ensure that all claims and technical data are current.



*Available on 1-3/4" and 2" only.
1000' minimum order requirement.