



CHILLER HOSE

Fluid Transfer Hose

BullDog premium lay-flat thermoplastic extruded through-the-weave Chiller Hose is lightweight and flexible. Chiller Hose is easy to manage, offers a long service life, and requires less storage space. The thermoplastic polyurethane provides exceptional abrasion and chemical resistance, and the high-strength woven reinforcement offers the high strength and flexibility needed for rental chiller installations. We have been the trusted supplier to some of the largest rental chiller outfits in the country, and with our experience, we can customize assemblies to meet your needs.

UNIQUE DESIGN FEATURES:

- Lower friction loss
- Reduces pumping costs
- Higher flow rates and further pumping distance
- Fast deployment and retrieval



Chiller Hose



 **AMERICAN MADE TOUGH.™**

Contact us today: 712.655.9201 · puck.com/industrial-equipment

CHILLER HOSE



FEATURES:

Improved Packability

Long-term storage in coiled configurations will have minimal impact on hose life.

Durable Construction

Features a unique through-the-weave one-piece construction comprising of a circular woven high tenacity polyester reinforcement totally encapsulated in a tough elastomeric polyurethane cover and lining.

Long Service Life

Designed for long life and maintenance-free service in even the harshest environments. Tough and durable with exceptional resistance to abrasion and cutting for use on a wide variety of ground conditions. Resistant to fuels, chemicals, UV, ozone, weathering, hydrolysis and microbiological attack.

Operating Temperature Range

-58°F to +158°F (-37°C to 70°C)

Low Operating Costs

A low-pressure loss for efficient pumping. Swells up to 10% above uncharged diameter at maximum operating pressure enabling more water to be pumped.

Additional Hardware

Wide range of couplings and hardware available for connecting the hose to additional segments, auxiliary hardware or equipment.

TECHNICAL SPECIFICATIONS:

Size	Pressure		Thickness	Wall Weight
	Working	Burst		
inch mm	psi kpa	psi kpa	inch mm	lbs/ft kg
2 51	300 1,379	600 4,137	.085 2.16	0.25 0.113
2-1/2 64	300 1,379	600 4,137	.095 2.41	0.37 0.168
3 76	300 1,379	600 4,137	.102 2.59	0.56 0.254
4 102	300 1,379	600 4,137	.125 3.18	0.80 0.363
6 152	300 1,379	600 4,137	.140 3.56	1.25 0.567
7-1/4 184	250 1,034	500 3,447	.190 4.83	1.90 0.862
8 203	300 1,379	600 4,137	.180 4.57	2.15 0.975
10 254	250 1,034	500 3,447	.185 4.70	2.80 1.270

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.

