

FIREPOWER

Aggressive Interior Attack Fire Hose

Firepower is an extremely durable double-jacketed hose made from a high-tech nylon-polyester outer jacket, with durability and flow that make it an invaluable firefighting tool. This product has excellent packing capabilities for a premium hose and improves hosehandling applications with an easy-to-grip material. Also featuring a high-performance, nitrile-rubberthrough-the-weave inner liner that offers superior burst pressure, Firepower delivers optimum kink resistance while providing greater flexibility and superior water flow with low friction loss. Firepower combines high abrasion resistance with low overall weight and low drag resistance. Designed with unrivaled UV and ozone protection, this product will bring you years of reliable service. Firepower is available in 5 NFPA colors.

UNIQUE DESIGN FEATURES:

- Easy-to-grip material
- Superior burst pressure
- Greater flexibility
- Superior water flow
- Low friction loss
- High abrasion resistance
- Low drag resistance
- High heat resistance
- UV and ozone protection
- Available in 5 NFPA colors



■ AMERICAN MADE TOUGH.[™] Contact us today: 712.655.9201 · puck.com/puck-fire



FIREPOWER



FEATURES:

Unrivaled Kink Resistance

Passes 34", 24", and 18" doorway kink test. Loops to 11" before kink, ensuring no line failure or loss of flow.

Six Times More Heat Resistance

Nitrile/PVC lining provides six times more heat resistance than conventional hoses, when subjected to BS6391 resistance test.

Water-Resistant Jacket

Firepower's innovative, uniquely-woven jacket minimizes water absorption and drying time, compared to traditional hose. This reduces the weight of a hose line in use, making it easier to transport and battle flames from any angle.

Unmatched Performance For CAFS operations.

Superior Abrasion Performance

Exceeds Standards

Firepower is manufactured to meet or exceed the NFPA 1961 standard.

ULC Listed

Available on 1-3/4" and 2-1/2" (400 PSI service pressure)

Temperature range -36°F to +158°F

TECHNICAL SPECIFICATIONS:

	Pressure					
Size	Service	Proof	Burst	Bowl Size	Weight (50'/15M)	Coil Diameter (50'/15M)
inch mm	psi kpa	psi kpa	psi kpa	inch	lbs kg	inch mm
1-3/4 45 (4)	500 3,500	1,000 7,000	1,500 10,500	2-1/8	18 8.1	16.5 419
2 50 UL	500 3,500	1,000 7,000	1,500 10,500	2-3/8	20 9.1	17.5 445
2-1/2 65	500 3,500	1,000 7,000	1,500 10,500	2-7/8	23 10.4	18.5 470

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.

