





Fuel & Water Delivery Hose

A premium flexible layflat hose designed for the transfer of fuel, wastewater, sewer, treated and reclaimed water. WAT-Hog features a unique through-the-weave one piece construction comprising a circular woven high tenacity polyester reinforcement totally encapsulated in a tough elastomeric polyurethane cover and lining. Designed for long life and maintenance free service in even the harshest environments. High flexibility and kink resistance allows natural ground contours to be followed without putting stress on the pipeline and eliminates expensive path cutting work.

TYPICAL APPLICATIONS:

Municipal

- Pipeline by-pass
- Waste transfer
- Testing/flushing water mains
- Sewer and water treatment
- Municipal fire services

Marine

- Cargo loading/unloading
- Supply ship to off shore facilities

Industrial

- High flow dewatering
- Liquid and powder transfer
- Slurry pumping
- Loading/unloading from truck
- Industrial fire services
- Portable chiller operation

Military

- Water transfer
- Fuel transfer



■ AMERICAN MADE TOUGH.■

Contact us today: 712.655.9201 · puck.com/industrial-equipment

WAT-HOG



FEATURES:

Long Service Life

Designed for long life and maintenance free service in even the harshest environments. Tough and durable with exceptional resistance to abrasion and cutting for use on a wide variety of ground conditions. No corrosion or scaling. Resistant to fuels, chemicals, UV, ozone, weathering, hydrolysis, and microbiological attack.

Durable Construction

Features a unique through-the-weave onepiece construction comprising a circular woven high tenacity polyester reinforcement totally encapsulated in a tough elastomeric polyurethane cover and lining.

Static Discharge Wires

Available with bonding wires, conforming to MIL-PRF-370 Type C, are fitted to allow couplings to be electrically bonded when transferring fuels.

Easy to Store and Transport

Long-term storage in coiled configurations will have minimal impact on hose life.

Additional Hardware

A wide range of couplings, manifolds, and hardware available for connecting the hose to additional segments, fluid supplies, or auxiliary hardware.

Low Operating Costs

A low-pressure loss for efficient pumping. Swells up to 10% above uncharged diameter at maximum operating pressure enabling more water to be pumped.

Fast Deployment and Retrieval

Long continuous lengths can be quickly deployed and retrieved using a wide variety of systems including light duty trailers, flaking boxes, and power-driven reels. High flexibility and kink resistance allows natural ground contours to be followed without putting stress on the pipeline and eliminates expensive path cutting work. Fewer and faster connections mean reduced labor and equipment costs.

TECHNICAL SPECIFICATIONS:

	Pressure		Wall		
Size	Standard Color	Working	Burst	Thickness	Weight
inch mm		psi kpa	psi kpa	inch mm	lbs/ft kg
2 51	Blue/Tan/Orange	300 2,100	600 4,200	.08 2.03	0.21 0.095
2-1/2 64	Blue/Tan/Orange	300 2,100	600 4,200	.08 2.03	0.30 0.136
3 74	Blue/Tan/Orange	300 2,100	600 4,200	.09 2.28	0.37 0.168
4 102	Blue/Tan/Orange	300 2,100	600 4,200	.09 2.28	0.56 0.254
6 152	Blue/Tan/Orange	300 2,100	600 4,200	.10 2.54	1.22 0.553
7-1/4 184	Blue/Tan/Orange	250 1,800	500 3,500	.16 4.06	1.89 0.859
8 200	Blue/Tan/Orange	250 1,800	500 3,500	.18 4.57	2.10 0.950
10 250	Blue/Tan/Orange	250 1,800	500 3,500	.20 5.08	2.85 1.290

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.

THROUGH-THE-WEAVE
ONE-PIECE CONSTRUCTION
PROVIDES EXTREME
DURABILITY ON HARSH
TERRAINS AS WELL AS
HIGH FLEXIBILITY AND
KINK RESISTANCE



