



AIR RAID

Air Raid hose is a lay-flat air hose designed for improved handling and long-term service. Air Raid features a through the weave nitrile-PVC rubber hose encapsulated by a high-tech nylon-polyester outer jacket. Air Raid offers excellent packability and superior kink resistance. After you use Air Raid, you will never want to go back to your old-style air hoses again.

# **UNIQUE DESIGN FEATURES:**

- · Hybrid construction offers great flexibility
- · Operating temperature -36° to +158° Fahrenheit
- Improved packability and lighter weight as compared to conventional air hoses
- High-quality raw materials and product construction offers excellent abrasion resistance and long life
- Resistant to a wide range of chemicals, including diesel and gasoline





Step up your water delivery!
Contact us today: 712.655.9201 · bulldoghose.com

# AIR RAID



## **FEATURES:**

**Lowest Friction Loss** Superior efficiency in the field, delivering more air with less kinking.

#### **Best-in-Class Adhesion**

Provides enhanced hose performance and increased hose life.

# **Improved Packability**

Compact and flexible.

## Lay-Flat Design

The flexibility of Air Raid's lay-flat design allows for ease in packing, unpacking and handling, delivering more efficiency to your operation.

### **Superior Abrasion Performance**

Through the weave nitrile-PVC rubber hose is encased in a nylonpolyester jacket that increases abrasion and chemical resistance.

Standard Color is Yellow

## **TECHNICAL SPECIFICATIONS:**

#### Pressure

Internal Diameter	Standard color	Max Working	Burst	End Tensile Strength	Wall Thickness	Weight
inch mm		psi bar	psi bar	lbs tons	inch mm	lbs/ft kg/m
2 50.8	Yellow	150 10.3	1,500 103.4	26,600 13,300	0.175 4.45	0.45 0.67

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.

