



Bulldog
HOSE COMPANY

AMERICAN MADE TOUGH.



AG HOSES



Pressure

Size inch mm	Working psi kpa	Burst psi kpa	End Tensile Strength lbs kg	Wall Thickness inch mm	Weight lbs/ft kg
MAINLINE					
7-1/4 184	250 1,724	500 3,447	70,000 31,750	0.22 5.59	2.30 1.04
8 203	250 1,724	500 3,447	80,000 36,287	0.18 4.57	2.25 1.02
10 254	250 1,724	500 3,447	96,000 43,545	0.20 5.08	2.85 1.29
ARMOUR GUARD®					
4 100	300 2,068	600 4,136	25,000 11,340	0.120 3.05	0.84 0.38
5 125	300 2,068	600 4,136	36,000 16,329	0.125 3.18	1.04 0.47
6 150	300 2,068	600 4,136	54,000 24,494	0.157 4.00	1.48 0.67
PREMIUM 200®					
3 76	300 1,378	600 4,136	20,000 9,072	0.115 2.92	0.60 0.27
4 100	300 1,378	600 4,136	25,000 11,340	0.120 3.05	0.84 0.38
4-1/2 114	300 1,378	600 4,136	32,000 14,515	0.150 3.80	0.94 0.43
5 125	300 1,378	600 4,136	36,000 16,329	0.125 3.18	1.04 0.47
X24 DRAG HOSE					
5 125	250 1,724	500 3,447	40,000 18,144	0.150 3.81	1.15 0.52
5-1/2 140	250 1,724	500 3,447	46,000 20,865	0.155 3.94	1.33 0.60
6 150	250 1,724	500 3,447	64,000 29,029	0.200 5.08	1.95 0.88
7-1/4 184	250 1,724	500 3,447	70,000 31,751	0.220 5.59	2.50 1.13

Bulldog Hose Company maintains ongoing product improvement and development programs. Therefore Bulldog reserves the right to modify any product or specification without prior notice. If necessary, please contact Bulldog Hose Company customer service to ensure that all claims and technical data are current.



Step up your fluid delivery!

Contact us today: 712.655.9201 · bulldoghose.com