



X24

Sludge Injection Drag Hose

Bulldog X24 is a high performance flexible lay flat hose for sludge injection and transfer of slurries, liquid manure and municipal sludge. Designed for both continuous and intermittent operation at high working pressures. X24's through-the-weave manufacturing technique prevents delamination and results in a much lower friction loss than aluminum or PVC pipe, reducing pumping costs. Swells in diameter enabling fluids to be pumped further and at higher flow rates. Raw materials, components and finished products are rigorously tested and inspected to ensure excellent product reliability.

TYPICAL APPLICATIONS:

- Sludge injection
- Slurry transfer
- Municipal sludge
- Liquid manure

UNIQUE DESIGN FEATURES:

- Lower friction loss
- Reduces pumping costs
- Higher flow rates and further pumping distance
- Fast deployment and retrieval



**Backed by BullDog's Irrigation
Hose One-Year Warranty.**
bulldoghose.com/resources



Step up your fluid delivery!

Contact us today: 712.655.9201 · bulldoghose.com

FEATURES:

- High Visibility**
Contrast of the light hose color makes it easier to see in the field.

Ease of Drag
Specifically designed to be pulled and dragged behind sludge injection vehicles that inject liquids into the soil for agricultural gain.
- Superior Abrasion Resistance**
Durable, abrasion resistant thermoplastic polyurethane construction for tough environments.

Unmatched Performance
Long, continuous lengths can be quickly deployed and retrieved using light duty or power-driven reels.
- Extreme Durability**
Features through-the-weave construction comprising a circular woven high tenacity polyester reinforcement, totally encapsulated in a tough, abrasion resistant, polyurethane cover and lining.

TECHNICAL SPECIFICATIONS:

Size	Pressure		Burst		End Tensile Strength		Wall Thickness		Weight	
	Working									
inch mm	psi kpa		psi kpa		lbs kg		inch mm		lbs/ft	kg
5 125	250 1,724		500 3,447		40,000 18,144		0.150 3.81		1.15	0.52
5-1/2 140	250 1,724		500 3,447		46,000 20,865		0.155 3.94		1.33	0.60
6 150	250 1,724		500 3,447		64,000 29,029		0.200 5.08		1.95	0.88
7-1/4 184	250 1,724		500 3,447		70,000 31,751		0.220 5.59		2.50	1.13

Bulldog Hose Company maintains ongoing product improvement and development programs. Therefore Bulldog reserves the right to modify any product or specification without prior notice. If necessary, please contact Bulldog Hose Company customer service to ensure that all claims and technical data are current.

